



[Home](#)[Configuration](#)[Statistics](#)[Tools](#)[Logs](#)[Accounts](#)[Quick Start](#)[Copyright](#)[Logoff](#)

Account: admin
Level: ADMINISTRATOR
Mode: Read-Write
Authentication Method: Local



[General](#) [IP](#) [Radio](#) [SNMP](#) [Quality of Service \(QoS\)](#) [Security](#) [Time](#) [VLAN](#) [DiffServ](#) [Protocol Filtering](#) [Port Configuration](#) [Syslog](#) [Unit Settings](#)

Configuration → Radio

5.7GHz SISO OFDM - Access Point - 0a-00-3e-38-8c-b5

Radio Configuration

Frequency Carrier :	<input type="text" value="5795.0"/>
Channel Bandwidth :	10.0 MHz
Cyclic Prefix :	<input type="text" value="One Sixteenth"/>
Color Code :	<input type="text" value="41"/> (0—254)
Subscriber Color Code Rescan (When not on a Primary Color Code) :	<input type="text" value="0"/> Minutes (0 — 43200)
Subscriber Color Code Wait Period for Idle :	<input type="text" value="0"/> Minutes (0 — 60)
Installation Color Code :	<input type="radio"/> Enabled <input checked="" type="radio"/> Disabled
Sector ID :	<input type="text" value="0"/>

Frame Configuration

Max Range : Miles (Range: 1 — 40 miles)

Downlink Data : % (Range: 10 — 90 %)

Contention Slots : (Range: 0 — 15)

Broadcast Repeat Count : (Range : 0 — 2)

Power Control

Transmit Power : dBm (Range: -30 — +20 dBm)

External Gain : dB (Range: 0 — +17 dB)

SM Receive Target Level : dBm (Range : -80 — -40 dBm)

Advanced

Receive Quality Debug : Enabled
 Disabled