

TCB**GRANT OF EQUIPMENT
AUTHORIZATION****TCB****Certification****Issued Under the Authority of the
Federal Communications Commission****By:****UL VS Ltd
Unit 3 Horizon, Wade Road, Kingsland
Business Park,
Basingstoke, RG24 8AH
United Kingdom****Date of Grant: 05/22/2015****Application Dated: 05/20/2015****Cambium Networks Limited
Unit B2 Linhay Business Park
Eastern Road
Ashburton, Devon, TQ13 7UP
United Kingdom****Attention: Don Reid , Mr****NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is
VALID ONLY for the equipment identified hereon for use under the Commission's
Rules and Regulations listed below.

FCC IDENTIFIER: QWP-50450I**Name of Grantee: Cambium Networks Limited****Equipment Class: Licensed Non-Broadcast Station Transmitter****Notes: Wireless Ethernet Bridge, Dual Channel OFDM
MIMO Combination Access Point, Subscriber Station
and Point to Point Equipment**

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
36 MO	90Y	4942.5 - 4987.5	0.25	2.3 PM	4M52G7D
36 MO	90Y	4945.0 - 4985.0	0.25	2.3 PM	9M10D7D
36 MO	90Y	4950.0 - 4980.0	0.23	2.3 PM	18M2D7D

Output power is conducted. This device supports MIMO operations as described in this filing. The device supports 5MHz, 10MHz, 20MHz, bandwidths. Professional installation is required for devices with external antenna connectors. To comply with RF exposure requirements antennas must be installed to ensure a minimum separation distance of 1.07m from persons and must not be co-located or operating in conjunction with any other antenna or transmitter except in accordance with accepted multi-transmitter product procedures.

36: Certain antennas used with this equipment require a minimum cable length, or have output power limitations as documented in the application.

MO: This Multiple Input Multiple Output (MIMO) device was evaluated for multiple transmitted signals as indicated in the filing.